admire[™]air 7000

one-touch air-threading coverlock machine

PFAFF Perfection starts here.[™]



TOP FEATURES

- 1. One-Touch Electronic Air-Threading Loopers With the PFAFF[®] admire[™] air 7000 one-touch air-threading feature, you can effortlessly thread the machine loopers with the simple push of a button.
- 2. Color Touchscreen Select your stitch, and the optimal thread tensions, recommended stitch length, and more are set automatically.
- **3. Exceptional Lighting** Exceptional illumination of the sewing area for optimal visibility 60% brighter than competition.*
- **4.** Free Arm The free arm provides easy access for smaller projects like cuffs, hems and children's clothing.
- 5. Knee Lift Hands-free presser foot lift for ease and control.
- 6. 26 Decorative and utility stitches using 5 / 4 / 3 / 2 thread sewing The 5/4/3/2 thread stitch capability provides 26 different stitch options for a wide range of stitch techniques.

SELL UP FEATURES FROM coverlock[™] 3.0

- **One-Touch Electronic Air-Threading Loopers** With the PFAFF[®] *admire*[™] air 7000 one-touch air-threading feature, you can effortlessly thread the machine loopers with the simple push of a button.
- **Color Touchscreen** Select your stitch, and the optimal thread tensions, recommended stitch length, and more are set automatically.
- **Exceptional Lighting** Exceptional illumination of the sewing area for optimal visibility 60% brighter than competition.*
- Free Arm The free arm provides easy access for smaller projects like cuffs, hems and children's clothing.
- Knee Lift Hands-free presser foot lift for ease and control.
- **26 Decorative and utility stitches using 5/ 4 / 3/ 2 thread sewing** The 5/4/3/2 thread stitch capability provides 26 different stitch options for a wide range of stitch techniques.





T 1	c	T II
Technique	Sewing	Talk about
AIR THREADING OVERLOCK LOOPERS	 Thread the thread guides and make sure to insert at least 1" in the upper looper threading hole, leaving a loose thread approx. 10". Show threading the upper and lower looper with the push of a button. 	 It has never been easier to thread and re-thread your machine. With just the push of a button the machine is threaded all the way through the loopers.
4- THREAD OVERLOCK	 Set a 4- thread overlock stitch Select 4-thread overlock stitch (stitch #3) Follow the recommendations in pop-up on screen to set for a 4-thread overlock stitch Medium weight woven fabric Differential feed 1 Keep settings as default Fold the medium weight woven fabric in half. Sew a seam cutting a little as you sew. 	 Why Buy a serger? The PFAFF[®] admire[™] air 7000 sews twice as fast as a regular sewing machine. See how all your edges will be perfectly finished without a chance of unraveling.
4- THREAD OVERLOCK	 Continue with 4- thread overlock stitch Medium weight stretch fabric (ribbing and sweatshirt fabric) Keep settings as default. Fold the ribbing in half lengthwise, stretch, and sew across the corner of a sweatshirt fleece square. Cut off the whole corner as you sew across. Fold up the bottom edge as for a blind hem. Sew with the cutter next to the fold, and the needles catching the fold, trimming the excess slightly. Optional: Turn hem upside down to show that you have a fast casing for elastic. Again move your hands away. 	 As you stretch the finished seam, talk about how a 4- thread overlock stitch stretches more than a regular sewing machine overlock stitch sewn on fabrics with stretch. Garments are so fast and easy when using the The PFAFF[®] admire[™] air 7000.





Technique	Sewing	Talk about
	Ŭ	
	 Continue with 4- thread overlock stitch Medium weight stretch fabric Change differential feed to 0.6 Keep stitch length 2.5 Sew along one edge of the sweater knit, cut very little as you sew 	 The differential feed feature is great for sewing on knits. The differential feed system consist of two sets of feed teeth arranged one behind the other. When the amount of feed by the front teeth is changed in relation to the feed by the rear feed teeth it will "stretch" or "gather" the
THE PARTY OF THE P	• Change Differential feed to 2 Sew along the opposite edge with the differential feed at 2.	 fabric. Use the differential feed to prevent stretching of knit fabrics and puckering of lightweight fabrics.
GATHERING	 Continue with 4- thread overlock stitch Light weight woven fabric Keep thread tension Set differential feed to 1 Set stitch length to 2.5 Left needle tension to 6.0 Right needle tension to 6.0 Sew a 3" (7-8 cm) thread chain Lengthen the stitch length to the longest stitch (5) Place the calico strip along the side of the cutter Sew along the edge of the fabric, cutting a little bit as you sew and hold your finger behind the foot so that the fabric bunches into your finger as you sew. This creates a more even and tighter gather. Sew another 3" chain at the end Adjust gathers. 	 You can gather fabrics quickly on the The PFAFF[®] admire[™] air 7000 by simply using the differential feed and stitch length adjustments. This gather is adjustable and much more consistent than drawing up basting threads on a regular sewing machine. Gathering this way is a great time saver. It finishes the edge at the same time that it gathers. You can adjust your stitch settings and save in the machine's memory for later use. There are 30 memories available for personal stitch settings.





Technique	Sewing	Talk about
TUBE-TURN	 Continue with 4- thread overlock Light weight stretch fabric (tricot) Go back to original default settings for the stitch again Sew a 6 – 8" (15-20 cm) thread chain. Bring chain around the foot to the front of the overlock machine. DO NOT cut chain off! Fold tricot around the chain. With the fold to the left and the bulk of the fabric to the right, sew with the fabric under the foot so you can see the fold to the left of the foot, cutting off most of the fabric. Leave the chain attached to the fabric. Pull the thread chain and the attached fabric through the tube. 	 It is easy to turn any sort of tube – even a small spaghetti strap or belt loop with the PFAFF® admire[™] air 7000. Use the thread chain as a built in pull!
ROLLED EDGE	 Change to 3- thread rolled edge (Stitch #14) Follow the recommendations in pop-up on screen to set for a 3-thread rolled edge Light weight woven fabric Keep settings as default Sew a rolled edge cutting a little as you sew. 	 The rolled edge is a fast and easy way to finish ruffles, napkins, or tablecloths. The rolled edge makes a wonderful finish with heavier decorative threads on home dec. projects such as valances and pillows.





Technique	Sewing	Talk about
COVERSTITCH, WIDE	 Select a wide coverstitch (Stitch #24) Follow the recommendations in pop-up on screen to set for a wide coverstitch Medium weight sweatshirt fabric Keep settings as default Fold under a hem on fabric Sew on the right side of fabric so that the folded hem raw edges is on the bottom and between the two needles 	 Hemming is done quickly on the PFAFF[®] admire[™] air 7000 coverlock machine by simply using one of the included coverstitches. The Coverstitch covers the raw edge of the hem on the underside, just like ready-towear. The Coverstitch straight stitch is on the top side. The Coverstich is available in two different widths, wide and narrow, and as a triple Coverstich.
CHAINSTITCH	 Select Chainstitch (Stitch #26) Follow the recommendations in pop-up on screen to set for a wide coverstitch Medium weight sweatshirt fabric Keep settings as default Sew a double Chainstitch on the wrong side of fabric Reduce presser foot pressure (if needed) for easier movement Pull the looper thread and show how easy it is to unravel the chainstitch when used as a basting stitch Set back to a four thread balanced stitch, to be ready for a new demo! 	 The PFAFF[®] admire[™] air 7000 coverlock machine also sews as a regular sewing machine. Use it to embellish with decorative threads.

PFAFF, PFAFF PERFECTION STARTS HERE, ADMIRE and COVERLOCK are trademarks of KSIN Luxembourg II, S.a.r.I. @2021 KSIN Luxembourg II, S.a.r.I. All rights reserved.